



◆ SPECIFICATION

Model	KHA-100SH20D	KHA-130SH20D	KHA-V200SH20D	KHA-S200SH20D	KHA-130SH20C	KHA-V200SH20C	KHA-S200SH20C	KHA-130SH20T	KHA-V200SH20T	KHA-S200SH20T
Camera										
Image Resolution	PAL: 25fps@720P(1280×720); NTSC: 30fps@720P(1280×720)	PAL: 25fps@960P(1280×960); NTSC: 30fps@960P(1280×960)	PAL: 25fps@1080P(1920×1080); NTSC: 30fps@1080P(1920×1080)	PAL: 25fps@1080P(1920×1080); NTSC: 30fps@1080P(1920×1080)	PAL: 25fps@960P(1280×960); NTSC: 30fps@960P(1280×960)	PAL: 25fps@1080P(1920×1080); NTSC: 30fps@1080P(1920×1080)	PAL: 25fps@1080P(1920×1080); NTSC: 30fps@1080P(1920×1080)	PAL: 25fps@960P(1280×960); NTSC: 30fps@960P(1280×960)	PAL: 25fps@1080P(1920×1080); NTSC: 30fps@1080P(1920×1080)	PAL: 25fps@1080P(1920×1080); NTSC: 30fps@1080P(1920×1080)
Effective Pixels	1280(H)×720(V), 1MP	1280(H)×960(V), 1.3MP	1920(H)×1080(V), 2MP	1920(H)×1080(V), 2MP	1280(H)×960(V), 1.3MP	1920(H)×1080(V), 2MP	1920(H)×1080(V), 2MP	1280(H)×960(V), 1.3MP	1920(H)×1080(V), 2MP	1920(H)×1080(V), 2MP
Image Resolution	PAL: 25fps@720P(1280×720); NTSC: 30fps@720P(1280×720)									
Effective Pixels	1280(H)×720(V), 1MP									
TV System	PAL/NTSC									
Electronic Shutter	1/25~1/50,000s, 1/30s~1/60,000s									
Sync System	Internal									
Usable Illumination	0.01Lux	0.001Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.001Lux	0.001Lux	0.01Lux
S/N Ratio	≥50dB									
Scanning System	Progressive Scan									
Video Output Mode	AHD/CVBS (720P) (BNC)	AHD/CVBS (960P) (BNC)	AHD/CVBS (1080P) (BNC)	AHD/CVBS (1080P) (BNC)	CVI(BNC)	CVI(BNC)	CVI(BNC)	TVI(BNC)	TVI(BNC)	TVI(BNC)
Lens										
Focus Length	3.6mm									
Focus Control	Fixed									
Lens Type	Fixed									
Pixels	2M Pixels									
Night Vision										
Infrared LED	① 5X24PCS									
Infrared Distance	20M									
IR Status	Under 10 Lux by CDS									
IR Power On	CDS Auto Control									
Camera Features										
Noise Reduction	3D NR	3D NR	3D NR	3D NR	3D NR	DNR	DNR	3D NR	DNR	DNR
OSD Support	Yes	Yes	Yes	Yes	No	No	No	No	No	No
General										
Vandalproof Housing	YES, Metal									
Lens Angle Adjustment	YES									
Dual Voltage	NO									
IR Cut Filter	YES									
Heater	NO									
Operation Temperature	-10℃ ~ +50℃ RH95% Max									
Storage Temperature	-20℃ ~ +60℃ RH95% Max									
Power Source	DC12V±10%, 500mA									
Dimension	① 94 x 69(H)mm									
Weight	0.40Kg									

Cantonk Corporation Limited

Add: 1-5/F, Building 3, Jiayuan Industrial Park, Economic & Technological Development Zone, Luogang District, 510530 Guangzhou, China
 Tel. No.: +86 20 6235 5288 Fax No.: +86 20 6235 5211 Homepage: http://www.cantonk.com Email: info@cantonk.com