



◆ SPECIFICATION

Model	KHA-100SL20D	KHA-130SL20D	KHA-V200SL20D	KHA-S200SL20D	KHA-130SL20C	KHA-V200SL20C	KHA-S200SL20C	KHA-130SL20T	KHA-V200SL20T	KHA-S200SL20T
<b>Camera</b>										
Image Resolution	PAL: 25fps@720P(1280*720); NTSC: 30fps@720P(1280*720)	PAL: 25fps@960P(1280*960); NTSC: 30fps@960P(1280*960)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@960P(1280*960); NTSC: 30fps@960P(1280*960)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@960P(1280*960); NTSC: 30fps@960P(1280*960)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)
Effective Pixels	1280(H)*720(V), 1MP	1280(H)*960(V), 1.3MP	1920(H)*1080(V), 2MP	1920(H)*1080(V), 2MP	1280(H)*960(V), 1.3MP	1920(H)*1080(V), 2MP	1920(H)*1080(V), 2MP	1280(H)*960(V), 1.3MP	1920(H)*1080(V), 2MP	1920(H)*1080(V), 2MP
Image Resolution	PAL: 25fps@720P(1280*720); NTSC: 30fps@720P(1280*720)									
Effective Pixels	1280(H)*720(V), 1MP									
TV System	PAL/NTSC									
Electronic Shutter	1/25~1/50,000s, 1/30~1/60,000s									
Sync System	Internal									
Usable Illumination	0.01Lux	0.001Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.001Lux	0.001Lux	0.01Lux
S/N Ratio	>50dB									
Scanning System	Progressive Scan									
Video Output Mode	AHD/CVBS (720P) (BNC)	AHD/CVBS (960P) (BNC)	AHD/CVBS (1080P) (BNC)	AHD/CVBS (1080P) (BNC)	CVI(BNC)	CVI(BNC)	CVI(BNC)	TVI(BNC)	TVI(BNC)	TVI(BNC)
<b>Lens</b>										
Focus Length	3.6mm									
Focus Control	Fixed									
Lens Type	Fixed									
Pixels	2M Pixels									
<b>Night Vision</b>										
Infrared LED	Φ5x24PCS									
Infrared Distance	20M									
IR Status	Under 10 Lux by CDS									
IR Power On	CDS Auto Control									
<b>Camera Features</b>										
Noise Reduction	3D NR	3D NR	3D NR	3D NR	3D NR	DNR	DNR	3D NR	DNR	DNR
OSD Support	Yes	Yes	Yes	Yes	No	No	No	No	No	No
<b>General</b>										
Vandalproof Housing	YES, Metal									
Lens Angle Adjustment	YES									
Dual Voltage	NO									
IR Cut Filter	YES									
Heater	NO									
Operation Temperature	-10℃ ~ +50℃ RH95% Max									
Storage Temperature	-20℃ ~ +60℃ RH95% Max									
Power Source	DC12V±10%, 500mA									
Dimension	Φ 94 x 69(H)mm									
Weight	0.45Kg									

Cantonk Corporation Limited  
 Add: 1-5/F, Building 3, Jiayuan Industrial Park, Economic & Technological Development Zone, Luogang District, 510530 Guangzhou, China  
 Tel. No.: +86 20 6235 5288 Fax No.: +86 20 6235 5211 Homepage: http://www.cantonk.com Email: info@cantonk.com