



SPECIFICATION

Model	KHA-100SHR30D	KHA-130SHR30D	KHA-V200SHR30D	KHA-S200SHR30D	KHA-130SHR30C	KHA-V200SHR30C	KHA-S200SHR30C	KHA-130SHR30T	KHA-V200SHR30C	KHA-S200SHR30C
Camera										
Image Sensor	OV9712S	IMX238	OV2710	IMX322	AR0130	OV2710	IMX322	IMX238	OV2710	IMX322
DSP	2431H	2431H	NVP2441H	NVP2441H	DH9801	FH8530C	FH8530C	FH8521	FH8531	FH8531
Image Resolution	PAL: 25fps@720P(1280*720); NTSC: 30fps@720P(1280*720)	PAL: 25fps@960P(1280*960); NTSC: 30fps@960P(1280*960)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@960P(1280*960); NTSC: 30fps@960P(1280*960)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@960P(1280*960); NTSC: 30fps@960P(1280*960)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)	PAL: 25fps@1080P(1920*1080); NTSC: 30fps@1080P(1920*1080)
Effective Pixels	1280(H)*720(V), 1MP	1280(H)*960(V), 1.3MP	1920(H)*1080(V), 2MP	1920(H)*1080(V), 2MP	1280(H)*960(V), 1.3MP	1920(H)*1080(V), 2MP	1920(H)*1080(V), 2MP	1280(H)*960(V), 1.3MP	1920(H)*1080(V), 2MP	1920(H)*1080(V), 2MP
TV System	PAL/NTSC									
Electronic Shutter	1/25~1/50,000s, 1/30~1/60,000s									
Sync System	Internal									
Usable Illumination	0.01Lux	0.001Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.001Lux	0.001Lux	0.01Lux
S/N Ratio	≥50dB									
Scanning System	Progressive Scan									
Video Output Mode	AHD/CVBS (720P) (BNC)	AHD/CVBS (960P) (BNC)	AHD/CVBS (1080P) (BNC)	AHD/CVBS (1080P) (BNC)	CVI(BNC)	CVI(BNC)	CVI(BNC)	TVI(BNC)	TVI(BNC)	TVI(BNC)
Lens										
Focus Length	2.8-12mm									
Focus Control	Manual									
Lens Type	Manual									
Pixels	2M Pixels									
Night Vision										
Infrared LED	∅ 5X36PCS									
Infrared Distance	30M									
IR Status	Under 10 Lux by CDS									
IR Power On	CDS Auto Control									
Camera Features										
Noise Reduction	3D NR	3D NR	3D NR	3D NR	3D NR	DNR	DNR	3D NR	DNR	DNR
OSD Support	Yes	Yes	Yes	Yes	No	No	No	No	No	No
General										
Vandalproof Housing	YES, Metal									
Lens Angle Adjustment	YES									
Dual Voltage	NO									
IR Cut Filter	YES									
Heater	NO									
Operation Temperature	-10℃ ~ +50℃ RH95% Max									
Storage Temperature	-20℃ ~ +60℃ RH95% Max									
Power Source	DC12V±10%, 700mA									
Dimension	∅ 131 x 93(H)mm									
Weight	0.80Kg									

Cantonk Corporation Limited

Add: 1-5/F, Building 3, Jiayuan Industrial Park, Economic & Technological Development Zone, Luogang District, 510530 Guangzhou, China
 Tel. No.: +86 20 6235 5288 Fax No.: +86 20 6235 5211 Homepage: http://www.cantonk.com Email: info@cantonk.com