

300FT RANGE 5.8GHz WIRELESS KIT



TRANSMIT VIDEO + AUDIO



WI 0300KIT58

Wireless Kit / 5.8GHz / 7 channels / Power supply included 6VDC for transmitter, 9VDC for Receiver

The AV sender is an excellent Audio / Video wireless transmitter at 5.8GHz with 7 channels. CCTV camera, Satellite Receiver, Set-Top-Box, DVD, and any other A/V device is available. SMA connector provides you to connect the high - gain antenna to acquire the best transmission.

- 5.8GHz frequency to transmit A/V signal Interference - Free.
- 7 - Channel for multiple transmission.
- Worldwide NTSC / PAL system applicable
- Cable - Free for AV transmission
- Digital LED display channel
- Simple installation and setup
- Long - distance transmission
- Expert in penetrating walls, floor, doors and so on
- High resolution, real time wireless video/audio
- Suitable for Surveillance, A/V transmission

CONTENTS

- Power supply included
1 x 6VDC for transmitter
1 x 9VDC for Receiver
- 1 x Transmitter
- 1 x Receiver
- 2 x Antenna

WI 0300KIT58 (Transmitter)	
Operation Frequency Range	5.725 - 5.875 GHz, 7 User Selectable Channels
Video Signal	NTSC and PAL
Channel Display	1 : 5.740 GHz 2 : 5.760 GHz 3 : 5.780 GHz 4 : 5.800 GHz 5 : 5.820 GHz 6 : 5.840 GHz 7 : 5.860 GHz
Display	Digital LED Display
Channel Setting	By Tact Switch
Audio / Video Connector	RCA connector
Antenna Connector	SMA Female
Memory Function	Full channel memory during power interruptions
Video Modulation Type	FM
Audio Modulation Type	FM - FM
Temperature range	-10 ~ +60°C
Dimension	3.4(L) x 4.6(W) x 1.3(H) inch 86(L) x 118(W) x 32(H) mm
Supply Voltage	DC 6V
Supply Current	800mA
Video Input Signal Level	1Vp-p, ±0.2V @ 75Ω
Audio Input Level	2Vp-p @ 10KΩ
Antenna Gain	5 dBi
WI 0300KIT58 (Receiver)	
Operation Frequency Range	5.725 - 5.875 GHz, 7 User Selectable Channels
Video Signal	NTSC and PAL
Channel Display	1 : 5.740 GHz 2 : 5.760 GHz 3 : 5.780 GHz 4 : 5.800 GHz 5 : 5.820 GHz 6 : 5.840 GHz 7 : 5.860 GHz
Display	Digital LED Display
Channel Setting	By Tact Switch
Input Signal Level Range	-10 dBm ~ -85 dBm
Audio / Video Connector	RCA connector
Antenna Connector	SMA Female
Memory Function	Full channel memory during power interruptions
Video Modulation Type	FM
Audio Modulation Type	FM-FM
Temperature range	-10 ~ +60°C
Dimension	3.4(L) x 4.6(W) x 1.3(H) inch 86(L) x 118(W) x 32(H) mm
Supply Voltage	DC 9V
Supply Current	300mA
Video Input Signal Level	1Vp-p, ±0.2V @ 75Ω
Audio Input Level	2Vp-p @ 10KΩ
Antenna Gain	5 dBi

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only, may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.