

A-HD

16 Channels

AUTO DETECTS ANALOG (D1/960H) & A-HD



- A-HD DVR only works with A-HD Cameras
- 16 CH 720p Real-Time Recording
- VGA / HDMI Output
- 4 CH Audio-in & 1 CH output

H.264



Back

FEATURES

- Full GUI with alpha blending
- Individual setting of resolution, frame rates & picture quality
- Instant Replay / Digital Zoom / Mouse Control
- Weekly scheduler with holiday by 10 minutes setting
- Covert, Disable and Private function of cameras
- Motion Detection with 576 area setting
- Relay alarm output
- PTZ control by RS-485
- Daylight Saving Time and Network Time Setting
- Multi User Authority up to 8 users
- Deinterlacer upon live and playback
- 22 languages with full graphic
- Individual Network port setting
- Auto Deletion
- Import and Export the configuration
- Interactive setup via network
- POS Interface
- Dual CODEC engine for independent video transmission

SMART
PHONE
COMPATIBLE
MR.PATROL



ACCESSORIES



Video	Video Input	16CH BNC
	Individual HD/ Analog Selectable	All Hybrid (Manual Setting, two channels pair)
	Available source	AHD 720p25,30/Composite/960H/Mixed
Audio	Output	1 HDMI (Main Display) / 1 VGA (Main Display)
	Audio Input	4 RCA
Sensor In	Output	1 RCA, 1 HDMI
	Alarm out	4 (NC, No Selectable)
Operating System		1 relay
Display		Embedded Linux OS
Main Recording	Speed	Real Time
	Resolution (Pixel)	1280X1024, 1280X720, 1920X1080
	Split screen	1, 4, 6, 8, 9, 13, 16
Playback	CODEC	H.264
	Resolution (Pixel)	720p (720p25, 30) / 960H, D1 (Composite, 960H)
	Speed	NTSC area: 240fps@720p, PAL area: 200fps@720p
Network	Display	1, 4, 6, 8, 9, 13, 16
	Search Mode	Calendar, Event, POS, Panorama, Thumbnail
	Speed	NTSC area: 120fps@720p, PAL area: 100fps@720p
Backup	Fast/Slow speed	Normal, REW & FF [recorded speed x2, x4, x8, x16,x32,x64, x1/2,x1/4], Frame to frame, Pause
	Network Interface	Megabit Ethernet
	Low Resolution	480x256 (720p25,30) / CIF (Composite, 960H)
The number of HDD	Speed	NTSC area: 240fps@480x256, PAL area: 200fps@480x256
	Interface	USB 2.0 X 2
Others	Backup Device	External HDD, CD&DVD-RW, Network, Thumb Drive
	Power	1 SATA
	Operating	24W
	Relative Humidity	5~40°C (41~104F)
Dimension		Maximum 80% non-condensing
		300(W) x 210(D) x 48(H) mm / 11.8(W) x 8.27(D) x 1.89(H) inches