

A-HD

4 Channels

AUTO DETECTS ANALOG (D1/960H) & A-HD



- A-HD DVR only works with A-HD Cameras
- 4 CH 720p Real-Time Recording
- VGA / HDMI Output
- 4 CH Audio-in & 1 CH output

H.264



Back

FEATURES

- Full GUI with alpha blending
- Individual setting of resolution, frame rates & picture quality
- Instant Replay / Digital Zoom / Mouse Control
- Weekly scheduler with holiday by 10 minutes setting
- Covert, Disable and Private function of cameras
- Motion Detection with 576 area setting
- Relay alarm output
- PTZ control by RS-485
- Daylight Saving Time and Network Time Setting
- Multi User Authority up to 8 users
- Deinterlacer upon live and playback
- 22 languages with full graphic
- Individual Network port setting
- Auto Deletion
- Import and Export the configuration
- Interactive setup via network
- POS Interface
- Dual CODEC engine for independent video transmission

**SMART
PHONE
COMPATIBLE**



MR.PATROL

ACCESSORIES



Video	Video Input	4CH BNC
	Individual HD/ Analog Selectable	All Hybrid (Manual Setting, two channels pair)
	Available source Output	AHD 720p25,30/Composite/960H/Mixed 1 HDMI (Main Display) / 1 VGA (Main Display)
Audio	Audio Input	4 RCA
	Output	1 RCA, 1 HDMI
Sensor In		4 (NC, No Selectable)
Alarm out		1 relay
Operating System		Embedded Linux OS
Display	Speed	Real Time
	Resolution (Pixel)	1280X1024, 1280X720, 1920X1080
	Split screen	1, 4
Main Recording	CODEC	H.264
	Resolution (Pixel)	720p (720p25, 30) / 960H, D1 (Composite, 960H)
	Speed	NTSC area: 60fps@720p, PAL area: 50fps@720p
Playback	Display	1, 4
	Search Mode	Calendar, Event, POS, Panorama, Thumbnail
	Speed	NTSC area: 30fps@720p, PAL area: 25fps@720p
	Fast/Slow speed	Normal, REW & FF [recorded speed x2, x4, x8, x16,x32,x64, x1/2,x1/4], Frame to frame, Pause
Network	Network Interface	Megabit Ethernet
	Low Resolution	480x256 (720p25,30) / CIF (Composite, 960H)
	Speed	NTSC area: 60fps@480x256, PAL area: 50fps@480x256
Backup	Interface	USB 2.0 X 2
	Backup Device	External HDD, CD&DVD-RW, Network, Thumb Drive
The number of HDD		1 SATA
Others	Power	24W
	Operating	5~40 °C (41~104F)
	Relative Humidity	Maximum 80% non-condensing
	Dimension	300(W) x 210(D) x 48(H) mm / 11.8(W) x 8.27(D) x 1.89(H) inches

MADE IN KOREA

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.