

A-HD

8 Channels

AUTO DETECTS ANALOG (D1/960H) & A-HD



- A-HD DVR only works with A-HD Cameras
- 8 CH 720p Real-Time Recording
- VGA / HDMI Output
- 4 CH Audio-in & 1 CH output

H.264



Back

FEATURES

- Full GUI with alpha blending
- Individual setting of resolution, frame rates & picture quality
- Instant Replay / Digital Zoom / Mouse Control
- Weekly scheduler with holiday by 10 minutes setting
- Covert, Disable and Private function of cameras
- Motion Detection with 576 area setting
- Relay alarm output
- PTZ control by RS-485
- Daylight Saving Time and Network Time Setting
- Multi User Authority up to 8 users
- Deinterlacer upon live and playback
- 22 languages with full graphic
- Individual Network port setting
- Auto Deletion
- Import and Export the configuration
- Interactive setup via network
- POS Interface
- Dual CODEC engine for independent video transmission

**SMART
PHONE
COMPATIBLE**



MR.PATROL

ACCESSORIES



Video	Video Input	8CH BNC
	Individual HD/ Analog Selectable	All Hybrid (Manual Setting, two channels pair)
	Available source Output	AHD 720p25,30/Composite/960H/Mixed 1 HDMI (Main Display) / 1 VGA (Main Display)
Audio	Audio Input	4 RCA
	Output	1 RCA, 1 HDMI
Sensor In		4 (NC, No Selectable)
Alarm out		1 relay
Operating System		Embedded Linux OS
Display	Speed	Real Time
	Resolution (Pixel)	1280X1024, 1280X720, 1920X1080
	Split screen	1, 4, 6, 8, 9
	CODEC	H.264
Main Recording	Resolution (Pixel)	720p (720p25, 30) / 960H, D1 (Composite, 960H)
	Speed	NTSC area: 120fps@720p, PAL area: 100fps@720p
	Playback	
Playback	Display	1, 4, 6, 8, 9
	Search Mode	Calendar, Event, POS, Panorama, Thumbnail
	Speed	NTSC area: 60fps@720p, PAL area: 50fps@720p
	Fast/Slow speed	Normal, REW & FF [recorded speed x2, x4, x8, x16,x32,x64, x1/2,x1/4], Frame to frame, Pause
Network	Network Interface	Megabit Ethernet
	Low Resolution	480x256 (720p25,30) / CIF (Composite, 960H)
	Speed	NTSC area: 120fps@480x256, PAL area: 100fps@480x256
Backup	Interface	USB 2.0 X 2
	Backup Device	External HDD, CD&DVD-RW, Network, Thumb Drive
The number of HDD		1 SATA
Others	Power	24W
	Operating	5~40 °C (41~104F)
	Relative Humidity	Maximum 80% non-condensing
	Dimension	300(W) x 210(D) x 48(H) mm / 11.8(W) x 8.27(D) x 1.89(H) inches